

Version: 1
Date of issue: 13.07.2021
Number of updates: 0
Data of updates: Page number: 1 of 7

SECTION 1.IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Trade name: GLICAR G13 CONCENTRATE

1.2. Relevant identified uses of the substance/mixture and uses advised against

Recommended use: Filling the cooling system of internal combustion engines after dilution with water

1.3. Details of the supplier of the safety data sheet

Company: Gli-therm Sp. z o.o.

ul. Rozwojowa 11, 44-338 Jastrzębie-Zdrój, Poland

Tel.: +48 533 798 833 biuro@gli-therm.pl www.gli-therm.pl

1.4. Emergency telephone number: +48 533 798 833

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Product classification:

Acute Tox. 4, H302, STOT RE 2, H373

Please consult chapter 16 of this SDS for full text of mentioned H phrases.

Physical and chemical hazards:

none.

Human health hazards:

- harmful if swallowed
- may cause damage to organs through prolonged or repeated exposure.

Environmental hazards:

none.

2.2. Label elements

Hazard pictograms:





Signal Word: WARNING

H Phrases:

H302 Harmful if swallowed

H373 May cause damage to organs through prolonged or repeated exposure

P Phrases:

P102 Keep out of reach of children P260 Do not breathe vapours/ spray

P264 Wash hands thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P301+P312 IF SWALLOWED: Call a POISON CENTRE/ doctor if you feel unwell

P314 Get medical advice/attention if you feel unwell

P501 Dispose of contents/container to hazardous or special waste collection point

Contents: Ethane-1,2-diol

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB at concentration equal to or greater than 0,1% by weight.



Version: 1
Date of issue: 13.07.2021
Number of updates: 0

Data of updates: 0
Page number: 2 of 7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

70.0% - 75.0% Ethane-1,2-diol

Index No: 603-027-00-1 CAS No: 107-21-1 EC No: 203-473-3

REACH No: 01-2119456816-28-0004 Acute Tox. 4, H302, STOT RE 2, H373

0.5% - 1.0% 2-Ethylhexanoic acid

Index No: 607-230-00-6 CAS No: 149-57-5 EC No: 205-743-6

- Repr. 2, H361d

0.5% - 1.0% Triethanolamine; 2,2',2"-nitrilotriethanol

Index No: – CAS No: 102-71-6 EC No: 203-049-8

REACH No: 01-2119486482-31-XXXX

This substance is not classified as dangerous.

Please consult chapter 16 of this SDS for full text of mentioned H phrases.

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

In case of Inhalation:

- remove to open air
- if breathing is irregular or stopped, administer artificial respiration
- in case of accident or unwellness, consult a doctor immediately and show him packing or label.

In case of skin contact:

- immediately take off all contaminated clothing
- immediately wash with plenty of water
- if irritation persists, obtain immediate medical attention
- wash contaminated clothing separately before using them again.

In case of eyes contact:

- remove contact lenses, if present
- irrigate copiously with clean, fresh water form at least 15 minutes
- if irritation persists, obtain immediate medical attention.

In case of Ingestion:

- rinse mouth thoroughly with water
- induce vomiting only if indicated by the doctor
- give nothing by mouth to an unconscious person
- get medical attention if any discomfort continues
- show this safety data sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Consumption and inhalation of product mist may cause irritation, headaches, nausea and breathing difficulties. Prolonged skin contact may cause redness and irritation. See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

suitable extinguishing media: chemical powders (type ABC or BC), CO2, foam, nebulized water

- extinguishing media which must not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

- do not inhale explosion and combustion gases
- burning produces heavy smoke (CO, CO₂)
- cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk
- cool containers exposed to flames with water until well after the fire is out.

5.3. Advice for firefighters

- use suitable breathing apparatus



Version: 1
Date of issue: 13.07.2021
Number of updates: 0
Data of updates: Page number: 3 of 7

- collect contaminated fire extinguishing water separately. This must not be discharged into drains
- move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- wear personal protection equipment
- remove all sources of ignition
- evacuate area
- provide adequate ventilation
- use appropriate respiratory protection.

6.2. Environmental precautions

- do not allow to enter into soil/subsoil; do not allow to enter into surface water or drains
- retain contaminated washing water and dispose it
- in case entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

- immediately remove the product using appropriate personal protective equipment
- eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage
- retain contaminated washing water and dispose it
- contain and collect spillage with non-combustible, absorbent material e.g. sand or earth
- flush contaminated area with plenty of water.

6.4. Reference to other sections

See also section 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

- use localized ventilation system
- do not smoke, do not use matches or lighters
- avoid breathing vapor
- avoid contact with eyes and skin
- wear personal protection equipment
- keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
- do not eat or drink while working, keep away from food, drink and feed, keep out of reach of children.

7.2. Conditions for safe storage, including any incompatibilities

- always keep the containers tightly closed, in a dry, cool and well-ventilated place (under 40 °C)
- keep only in the original container
- keep containers upright
- keep away from food, drink and feed
- keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
- cool and adequately ventilated
- do not store with incompatible substances (see section 10).

7.3. Specific end use(s)

See section 1.2.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limit values:

Ethane-1,2-diol:

LTEL/8h: 20 ppm – 52 mg/m³ (Skin) STEL: 40 ppm – 104 mg/m³ (Skin)

DNEL - Ethane-1,2-diol:

Application Area Exposure routes Health effect Value Workers Skin contact Long-term systemic effects 106 mg/kg BW/d Long-term local effects Workers Inhalation 35 mg/m³ 53 mg/kg BW/d Consumers Skin contact Long-term systemic effects Long-term local effects 7 mg/m³ Consumers Inhalation

DNEL - Triethanolamine:

Application Area Exposure routes Health effect Value Workers Skin contact Long-term systemic effects 3.1 mg/kg BW/d Workers Inhalation Long-term systemic effects 1.25 mg/m³ Workers Long-term systemic effects 13 mg/m³ BW/d Oral



Version: 1
Date of issue: 13.07.2021
Number of updates: 0
Data of updates: –

4 of 7

Page number:

Inhalation 1.25 mg/m³ Workers Long-term local effects Consumers Skin contact Long-term systemic effects 6.3 mg/kg BW/d 5 mg/m³ Inhalation Long-term systemic effects Consumers Consumers Inhalation Long-term local effects 5 mg/m³

PNEC - Ethane-1,2-diol:

CompartmentValueFresh water10 mg/lMarine water1 mg/lAquatic intermittent release10 mg/lFresh water sediment20.9 mg/kgSoil1.53 mg/kgSewage treatment plant199.5 mg/l

PNEC - Triethanolamine:

Compartment Value Fresh water 0.32 mg/l Marine water 0.032 mg/l 5.12 mg/l Aquatic intermittent release Sewage treatment plant 10 mg/l Fresh water sediment 0.17 mg/kg Marine water sediment 0.17 mg/kg Soil 0.151 mg/kg

8.2. Exposure controls

Eye protection:

- use close fitting safety goggles, masks suitable for the product.

Protection for skin and hands:

- wear protective gloves, protective clothing. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Respiratory protection:

- use adequate protective respiratory equipment
- good ventilation is essential when handling this material do not breathe vapour
- in case of mist or spray exposure wear suitable personal respiratory protection (breathing mask) and protective suit.

Thermal Hazards:

None.

Environmental exposure controls:

- do not allow to enter into soil/subsoil; do not allow to enter into surface water or drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

(a) Physical state: homogeneous liquid, without sediments

(b) Colour: various (c) Odour: N.A.

(d) Melting point/freezing point: -36 °C (after dilution with water 1:1)

e) Boiling point or initial boiling point and boiling

range: > 180 °C (f) Flammability: N.A.

(g) Lower and upper explosion limit: 3.2% vol./15.3% vol. (Ethane-1,2-diol)

(h) Flash point: 111 °C

(i) Auto-ignition temperature: 398 °C (Ethane-1,2-diol)

(j) Decomposition temperature:

(k) pH:

(l) Kinematic viscosity:

(m) Solubility:

N.A.

N.A.

(n) Partition coefficient n-octanol/water (log value):
-1.36 (Ethane-1,2-diol)
(o) Vapour pressure:
(p) Density and/or relative density:
-1.36 (Ethane-1,2-diol)
0,123 hPa (25 °C)
1.140-1.160 g/cm³

q) Relative vapour density: 2.14 (Air = 1) (Ethane-1,2-diol)

(r) Particle characteristics: Not applicable

9.2. Other information

Other solvents: alcohol, acetone, ether.

Dynamic viscosity: 16.1 mPas (20 °C) (Ethane-1,2-diol)

Critical temperature: 446 °C (Ethane-1,2-diol)



Version: 13.07.2021 Date of issue: Number of updates: 0 Data of updates: Page number: 5 of 7

SECTION 10. STABILITY AND REACTIVITY

Reactivity 10.1.

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

N.A.

10.4. Conditions to avoid

keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

avoid accumulating electrostatic charge

avoid contact with moisture.

Incompatible materials 10.5.

strong oxidizing

strong bases and acids.

10.6. Hazardous decomposition products

None.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

a) Acute toxicity:

Harmful if swallowed.

Mixture:

300 < ATEmix ≤ 2000 (mg/kg bodyweight) Oral:

Ethane-1,2-diol:

Rat LD₅₀ 7112 mg/kg Oral: Skin: Rat $LD_{50} > 3500 \text{ mg/kg}$ Inhalation: Rat $LC_{50} > 2.5 \text{ mg/l}$

b) Skin corrosion/irritation:

c) Serious eye damage/irritation:

d) Respiratory or skin sensitization:

e) Germ cell mutagenicity:

N.A.

f) Carcinogenicity:

g) Reproductive toxicity:

N.A.

h) STOT-single exposure:

N.A.

i) STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

j) Aspiration hazard:

11.2. Information on other hazards:

None.

SECTION 12. ECOLOGICAL INFORMATION

Adopt good working practices, so that the product is not released into the environment. Prevent product entering water courses, sewers and prevent penetration of the product into the earth.

12.1. **Toxicity:**

N.A.

Ethane-1,2-diol:

EC₅₀: 13 900-57 600 mg/l - toxicity to Daphnia magna, 48h

EC₅₀: 6 500-13 000 mg/l - toxicity to Pseudokirchneriella subcapitata, 96h



Version: 1
Date of issue: 13.07.2021
Number of updates: 0
Data of updates: –

6 of 7

Page number:

LC₅₀: 72 860 mg/l - toxicity to fish *Pimephales promelas*, 96h NOEC: 15 380 mg/l - toxicity to fish Pimephales promelas, 7d

12.2. Persistence and degradability:

N.A.

12.3. Bioaccumulative potential:

N.A..

12.4. Mobility in soil:

N.A.

12.5. Results of PBT and vPvB assessment:

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties:

Information not available.

12.7. Other adverse effects:

Information not available.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods:

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14. TRANSPORT INFORMATION

14.1.	UN number or ID number:	N.A.
14.2.	UN proper shipping name:	N.A.
14.3.	Transport hazard class(es):	N.A.
14.4.	Packing group:	N.A.
14.5.	Environmental hazards:	N.A.
14.6.	Special precautions for user:	N.A.

14.7. Maritime transport in bulk according to IMO instruments: N.A.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- 1. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing
- 2. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
- 3. COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

15.2. Chemical safety assessment

No.

SECTION 16. OTHER INFORMATION

This document was prepared by a competent person who has received appropriate training. This safety data sheet has been prepared on the basis of data provided by the manufacturer.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This document must not be regarded as a guarantee on any specific product property

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

IMDG: International Maritime Code for Dangerous Goods.

EC50: Half maximal effective concentration



Version: 13.07.2021 Date of issue: Number of updates: 0 Data of updates: Page number: 7 of 7

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population. STOT: Specific Target Organ Toxicity.

TLV TWA: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard)

Acute Tox. 4 Acute toxicity 4

Reproductive toxicity 2 Repr. 2

STOT RE 2 Specific target organ toxicity — repeated exposure 2

Full text of phrases referred to in Section 3:

Harmful if swallowed

Suspected of damaging the unborn child H361d

May cause damage to organs through prolonged or repeated exposure H373

This document was prepared by: CHEMIKOS; www.chemikos.pl; e-mail: biuro@chemikos.pl